



Precision Plumbing Products
"Specify with Confidence - Install with Pride"

LEAD FREE

**NICKEL PLATED
 FLUID HAMMER ARRESTORS**

www.pppinc.net



Dimensional & Air Loading Data

PART NUMBER	A OAL	B NPT	NITROGEN PRELOAD PSI
SNP-500	5"	1/2" brass	60
SNP-750	6"	3/4" brass	60
SNP-1000	6 3/4"	1" brass	60
SNP-1250	9 1/2"	1" brass	60
SNP-1500	11 1/4"	1" brass	60
SNP-2000	12"	1" brass	60

No Access Panel Required.

Consult Local Code.

PROJECT SUBMITTAL

Water Hammer Arrestors (Nickel Plated)

Normal operating pressure 0 to 80 PSIG.
 Spike pressure not to exceed 400 PSIG.

Arrestor Construction:

Threaded Adapter:

Machined of C69300 ECO Lead Free Brass.
 Type L copper barrel, Composite Material, Nitrile "O" rings, Brass or Copper Cap depending on size. All parts 100% Nickel Plated.

Application:

Sea water, Petroleum, Chemicals and Corrosive fluids.
 Available in NPT or BSP threads.
 Manufacturing lead time: 4-6 weeks.

Project: _____

Contractor: _____

Engineer: _____

Date Submitted: _____

Prepared By: _____

Over 40 years of outstanding performance



JL Industries, Inc.

Precision Plumbing Products

Division of JL Industries, Inc.

802 SE 199th Avenue
 Portland, Oregon 97233

T (503) 256-4010
 F (503) 253-8165

www.pppinc.net

