



Precision Plumbing Products

"Specify with Confidence - Install with Pride"

LEAD FREE

**CPVC
FLUID HAMMER ARRESTORS**

www.pppinc.net



PART NUMBER	SIZE (NPT)
CPVC-500	1/2"
CPVC-750	3/4"
CPVC-1000	1"
CPVC-1500	1 1/2"
CPVC-2000	2"
CPVC-3000	3"
CPVC-4000	4"

DESCRIPTION: SCH.#80 Gray
(For all parts shown.)

No access panel required.

Consult Local Code.

PROJECT SUBMITTAL

Project: _____

Contractor: _____

Engineer: _____

Date Submitted: _____

Prepared By: _____

CPVC Hammer Arrestors (pigmented)

The CPVC arrestor has been designed to protect the fittings and joints from the destructive hydraulic shock caused by quick closing solenoid valves - valves often found in commercial/industrial applications.

Applications include:

Acids, petroleum products, corrosive fluids, distilled and triple distilled waters, or where high temperature fluids (not to exceed 100° F) may be present.

Manufacturer's specifications:

All sizes manufactured from Schedule 80 material.
Pigmented CPVC conforms to ASTM Standard 1784 for materials and f-411 for pipe.
CPVC (Hi-Temp.) = Type IV Grade 1 = 4120 = Cell classification 23447-B.
Max operating pressure 100 PSIG.
Max temperature 100° F.

**40 Years
of outstanding performance**

For further information:

Contact your local Precision Plumbing Products representative, or contact the factory directly. We will help you to determine your individual needs and give you a quotation at no obligation.

U.S. Patent No. 3,633,627



Precision Plumbing Products

Division of JL Industries, Inc.

802 SE 199th Avenue
Portland, Oregon 97233

T (503) 256-4010
F (503) 253-8165

www.pppinc.net

