



Precision Plumbing Products

"Specify with Confidence - Install with Pride"

PRECISION PRIMING ADAPTER



ABS or PVC Tapped P-Trap Adapter

The PPA Adapter will cement inside a standard P-trap and is available in 2", 3" and 4" sizes.

A 1/2" or 5/8" brass compression fitting or 5/8" PTC (push to connect) fitting is provided with each adapter for the attachment to a drain trap water make-up line.

It provides a 360° adjustment prior to cementing in place. It meets ASTM D-2661 or ASTM D-2665 Standards. ABS and PVC materials schedule #40 DWV.

Features:

- Cuts Installation Costs
- Adjustable 360° Primer Line Attachment
- Eliminates No-hub Tapped P-trap
- 2 ABS/NH Adaptors & 2 NH Couplings or PVC/NH Adaptor
- Professional Appearance
- 1/2" or 5/8" Brass Compression Fitting or 5/8" PTC Fitting Supplied for Primer Line Attachment
- UPC/IAPMO Listed #2275

- PPA-2A and PPA-2P are 4" OAL**
 2" ID at bottom
 2 11/16" OD at top
 2 11/16" from bottom to center of inlet.
- PPA-3A and PPA-3P are 5 11/16" OAL**
 3" ID at bottom
 4" OD at top
 3 3/16" from bottom to center of inlet.
- PPA-4A and PPA-4P are 7" OAL**
 4" ID at bottom
 5 1/16" OD at top
 4 1/4" from bottom to center of inlet.

PROJECT SUBMITTAL

Project: _____

Contractor: _____

Engineer: _____

Date Submitted: _____

Prepared By: _____

Model #: _____

Part #:	Description ABS x Comp.	Part #:	Description PVC x Comp.
PPA-2A500	2" x 1/2" OD	PPA-2P500	2" x 1/2" OD
PPA-3A500	3" x 1/2" OD	PPA-3P500	3" x 1/2" OD
PPA-4A500	4" x 1/2" OD	PPA-4P500	4" x 1/2" OD
PPA-2A625	2" x 5/8" OD	PPA-2P625	2" x 5/8" OD
PPA-3A625	3" x 5/8" OD	PPA-3P625	3" x 5/8" OD
PPA-4A625	4" x 5/8" OD	PPA-4P625	4" x 5/8" OD
PPA-2A625PTC	2" x 5/8" OD	PPA-2P625PTC	2" x 5/8" OD
PPA-3A625PTC	3" x 5/8" OD	PPA-3P625PTC	3" x 5/8" OD
PPA-4A625PTC	4" x 5/8" OD	PPA-4P625PTC	4" x 5/8" OD

Precision Plumbing Products

Division of JL Industries, Inc.

802 SE 199th Avenue
 Portland, Oregon 97233

T (503) 256-4010
 F (503) 253-8165

www.pppinc.net



JL Industries, Inc.

