



Precision Plumbing Products
"Specify with Confidence - Install with Pride"

Trap Seal Protective Device

The GD series waterless trap device allows the flow of water and most debris while restricting pathogens, gasses, odors and pests. patent design allows for the flow of water and debris, while blocking gases, odors and pests.

This series of inline floor drain trap seals have a UV resistant ABS plastic frame, silicone rubber sealing flapper and four flexible sealing ribs. The GD series, like all waterless options should not be used in lieu of a trap primer. Waterless trap seals provide increased protection against evaporation and pests. This drain device is eco-friendly.

APPLICATIONS for:

- Residential
- Offices
- Hotels
- Hospitals
- Commercial
- Restaurants
- Industrial
- Maritime
- Pest Control
- Schools and Universities

MODEL NO's:

GD 2

Pipe Size: 2" (50-58 mm) Height: 2" (51mm)
 Flow Rate: 45 L/M | 12 GPM

GD 3

Pipe Size: 3" (75-85 mm) Height: 2" (51mm)
 Flow Rate: 128.7 L/M | 33.9 GPM

GD 4

Pipe Size: 4" (102-110 mm) Height: 2" (51mm)
 Flow Rate: 276.3 L/M | 73 GPM



Not to be used in lieu of a trap primer.

It's used in the outlet connections of floor drain bodies, or the inside of floor drain strainers to seal the opening to prevent odors, sewer gases, and insects from entering up through the floor drain grate. The drain trap seal has four flexible silicone sealing ribs to ensure easy installation into openings that have variations in size. The drain trap will open to allow drainage and close when there is no water flow.

PROJECT SUBMITTAL MODEL # _____

Project: _____

Contractor: _____

Engineer: _____

Date Submitted: _____

Prepared By: _____



Precision Plumbing Products

802 SE 199th Ave
 Portland, Oregon 97233
 T (503) 256-4010
 F (503) 253-8165
 www.pppinc.net